



**DUNCAN**

## SEED DRILLS ROLLER DRILL & ROLLER

### FEATURES

All Duncan Roller Drills and Rollers come with the following features standard :

- Rubber encased roller axle bearings
- 3" roller axles
- Jack stand
- Safety chains on drawbar
- Deflector tabs on each end of the frame
- Turnbuckle for drawbar adjustment
- Safety support chain for transport
- Agitator shaft and vees in bottom of boxes (Roller Drill only)
- Weigh kit (Roller Drill only)

Optional Equipment

- Standard or deep vee rings
- Hydraulic wheels
- Rear tow hitch
- Rear hydraulics
- Seed level indicators (for seed bins)

### DIMENSIONS

Roller Drill	8ft	9ft	10ft
Working width	2455mm	2780mm	3105mm
Overall width	2800mm	3125mm	3455mm
Length	4170mm	4170mm	4170mm
Height (with wheels up)	2010mm	2010mm	2010mm
Weight (unladen)	2080kg	2340kg	2600kg
Box capacity (approx)	393L	441L	488L

Roller	8ft	9ft	10ft
Working width	2455mm	2780mm	3105mm
Overall width	2800mm	3125mm	3455mm
Length	4170mm	4170mm	4170mm
Weight	1830kg	2040kg	2250kg

In accordance with the company's policy of continuous improvement to its machines, alterations in specifications may be made without notice. The company accepts no responsibility for any discrepancies which may occur between specifications of its machines and the descriptions thereof contained in this publication.

### MARKETED BY:



Built to work.

DUNCAN AG NEW ZEALAND  
PO BOX 2018, WASHDYKE, TIMARU  
PH: (03) 688 2029 FAX: (03) 688 2821

DUNCAN AG AUSTRALIA  
4B SILVERTON CLOSE, NORTH LAVERTON, VICTORIA 3026  
PH: (03) 9314 9666 FAX: (03) 9314 6810

Email: [admin@DuncanAg.co.nz](mailto:admin@DuncanAg.co.nz)  
[www.DuncanAg.co.nz](http://www.DuncanAg.co.nz)

### DEALERS NATIONWIDE:

**DUNCAN**

**ROLLER DRILL & ROLLER**



**DUNCAN**  
SEED DRILLS



**ROLLER DRILL & ROLLER**

**BUILT TO WORK**



Option of hydraulic rear wheels



Hydraulically operated clutch for engaging and disengaging the drive



High underbody clearance for transport



Safety support chain for transport with easy to remove pin



Rubber encased roller bearing to help eliminate shock and axle flexing




Easy to adjust variable speed gearbox



Deflector tabs on end of roller



Rubber encased roller bearing and 3" axle



Seed is diverted into this tray for easy and accurate calibration



Agitator shaft is standard to help prevent seed compaction and vees for better seed flow



Easy to adjust drawbar pitch with this turnbuckle



**ROLLER DRILL**

**BUILT TO WORK**



**ROLLER**

**BUILT TO WORK**